

MASARYKOVA UNIVERZITA
PŘÍRODOVĚDECKÁ FAKULTA
ÚSTAV MATEMATIKY A STATISTIKY

Bakalářská práce

Brno 2015

Jane Doe



MASARYKOVA UNIVERZITA
PŘÍRODOVĚDECKÁ FAKULTA
ÚSTAV MATEMATIKY A STATISTIKY



Principy matematické sazby v programu T_EX

Bakalářská práce

Jane Doe

Vedoucí práce: John Smith

Brno 2015

Bibliografický záznam

Autor: Jane Doe
Přírodovědecká fakulta, Masarykova univerzita
Ústav matematiky a statistiky

Název práce: Principy matematické sazby v programu TeX

Studijní program: Matematika

Obor: Finanční a pojistná matematika

Vedoucí práce: John Smith

Akademický rok: 2015/2016

Počet stran: 19

Klíčová slova: klíčové slovo 1, klíčové slovo 2, ...

Bibliographic entry

Author: Jane Doe
Faculty of Science, Masaryk University
Department of Mathematics and Statistics

Title of Thesis: The Principles of the Typesetting of Mathematics in TeX: the Program

Degree Programme: Mathematics

Field of study: Financial and Insurance Mathematics

Supervisor: John Smith

Academic Year: 2015/2016

Number of Pages: 19

Keywords: keyword1, keyword2, ...

Abstrakt

This is the abstract of my thesis, which can span multiple paragraphs.

Abstract

This is the English abstract of my thesis, which can span multiple paragraphs.

Místo tohoto listu vložte kopii oficiálního podepsaného zadání práce.

Poděkování

This is the acknowledgement for my thesis, which can span multiple paragraphs.

Prohlášení

Prohlašuji, že jsem svoji bakalářskou práci vypracovala samostatně s využitím informačních zdrojů, které jsou v práci citovány.

Jane Doe

Contents

1	Introduction	1
2	These are	3
	2.1 <i>the available</i>	3
	2.1.1 sectioning commands.	3
3	Floats and references	5
4	Mathematical equations	7
5	We have several <code>FONTS</code> <i>at disposal</i>	9
6	Inserting the bibliography	11
	Bibliography	13
7	Inserting the index	15
	Index	17
A	An appendix	19

List of Tables

3.1 A weather forecast 6

List of Figures

- 3.1 The logo of the Masaryk University at 40 mm 5
- 3.2 The logo of the Masaryk University at $\frac{2}{3}$ and $\frac{1}{3}$ of text width 6

1 Introduction

Theses are rumoured to be the capstones of education, so I decided to write one of my own. If all goes well, I will soon have a diploma under my belt. Wish me luck!

Říká se, že závěrečné práce jsou vyvrcholením studia a tak jsem se rozhodl jednu také napsat. Pokud vše půjde podle plánu, odnesu si na konci semestru diplom. Držte mi palce!

Hovorí sa, že záverečné práce sú vyvrcholením štúdia a tak som sa rozhodol jednu tiež napísať. Ak všetko pôjde podľa plánu, odnesiem si na konci semestra diplom. Držte mi palce!

Man munkelt, dass die Dissertation die Krönung der Ausbildung ist. Deshalb habe ich mich beschlossen meine eigene zu schreiben. Wenn alles gut geht, bekomme ich bald ein Diplom. Wünsch mir Glück!

Говорят, что тезис – это кульминация обучения. Поэтому я и решил написать собственный тезис. Если всё сработает по плану, я скоро получу диплом. Желайте мне удачи!

2 These are

2.1 the available

2.1.1 sectioning commands.

Paragraphs and

subparagraphs are available as well. Inside the text, you can also use unnumbered lists,

- such as
- this one
 - and they can be nested as well.
 - » You can even turn the bullets into something fancier,
 - § if you so desire.

Numbered lists are

1. very
 - (a) similar

and so are description lists:

Description list A list of terms with a description of each term

The spacing of these lists is geared towards paragraphs of text. For lists of words and phrases, the paralist package offers commands

- that
 - are
 - * better
 - suited
- 1. to
 - (a) this
 - i. kind of
 - A. content.

2. THESE ARE

The `amsthm` package provides the commands necessary for the typesetting of mathematical definitions, theorems, lemmas and proofs.

Theorem 2.1.1. *This is a theorem that offers a profound insight into the mathematical sectioning commands.*

Theorem 2.1.2 (Another theorem). *This is another theorem. Unlike the first one, this theorem has been endowed with a name.*

Lemma 2.1.3. *Let us suppose that $x^2 + y^2 = z^2$. Then*

$$\left\langle u \left| \sum_{i=1}^n F(e_i, v) e_i \right. \right\rangle = F\left(\sum_{i=1}^n \langle e_i | u \rangle e_i, v\right). \quad (2.1)$$

Proof. $\nabla^2 f(x, y) = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2}$. □

Corrolary 2.1.4. *This is a corrolary.*

Remark. This is a remark.

3 Floats and references

The logo of the Masaryk University is shown in Figure 3.1 and Figure 3.2 at pages 5 and 6. The weather forecast is shown in Table 3.1 at page 6. The following chapter is Chapter 4 and starts at page 7. Items 3, 3b, and 3(c)iv are starred in the following list:

1. some text
2. some other text
3. ★
 - (a) some text
 - (b) ★
 - (c) some other text
 - i. some text
 - ii. some other text
 - iii. yet another piece of text
 - iv. ★
 - (d) yet another piece of text
4. yet another piece of text

If your reference points to a place that has not yet been typeset, the `\ref` command will expand to `??` during the first run of `pdflatex sci-pdflatex.tex` and a second run is going to be needed for the references to resolve. With online services – such as Overleaf – this is performed automatically.



Figure 3.1: The logo of the Masaryk University at 40 mm



Figure 3.2: The logo of the Masaryk University at $\frac{2}{3}$ and $\frac{1}{3}$ of text width

Day	Min Temp	Max Temp	Summary
Monday	13°C	21°C	A clear day with low wind and no adverse current advisories.
Tuesday	11°C	17°C	A trough of low pressure will come from the north-west.
Wednesday	10°C	21°C	Rain will spread to all parts during the morning.

Table 3.1: A weather forecast

4 Mathematical equations

\TeX comes pre-packed with the ability to typeset inline equations, such as $e^{ix} = \cos x + i \sin x$, and display equations, such as

$$\mathbf{A}^{-1} = \begin{bmatrix} a & b \\ c & d \end{bmatrix}^{-1} = \frac{1}{\det(\mathbf{A})} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix} = \frac{1}{ad - bc} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix}.$$

\LaTeX defines the automatically numbered equation environment:

$$\gamma Px = PAx = PAP^{-1}Px. \quad (4.1)$$

The package `amsmath` provides several additional environments that can be used to typeset complex equations:

1. An equation can be spread over multiple lines using the `multline` environment:

$$\begin{aligned} a + b + c + d + e + f + b + c + d + e + f + b + c + d + e + f \\ + f + g + h + i + j + k + l + m + n + o + p + q \end{aligned} \quad (4.2)$$

2. Several aligned equations can be typeset using the `align` environment:

$$a + b = c + d \quad (4.3)$$

$$u = v + w + x \quad (4.4)$$

$$i + j + k + l = m \quad (4.5)$$

3. The `alignat` environment is similar to `align`, but it doesn't insert horizontal spaces between the individual columns:

$$a + b + c + d \quad = 0 \quad (4.6)$$

$$e + f + g = 5 \quad (4.7)$$

4. Much like chapter, sections, tables, figures, or list items, equations – such as (4.8) and (My equation) – can also be labeled and referenced:

$$b_{11}x_1 + b_{12}x_2 + b_{13}x_3 \quad = y_1, \quad (4.8)$$

$$b_{21}x_1 + b_{22}x_2 \quad + b_{24}x_4 = y_2. \quad (\text{My equation})$$

4. MATHEMATICAL EQUATIONS

5. The gather environment makes it possible to typeset several equations without any alignment:

$$\psi = \psi\psi, \tag{4.9}$$

$$\eta = \eta\eta\eta\eta\eta\eta, \tag{4.10}$$

$$\theta = \theta. \tag{4.11}$$

6. Several cases can be typeset using the cases environment:

$$|y| = \begin{cases} y & \text{if } z \geq 0, \\ -y & \text{otherwise.} \end{cases} \tag{4.12}$$

For the complete list of environments and commands, consult the `amsmath` package manual¹.

1. See <http://mirrors.ctan.org/macros/latex/required/amslatex/math/amslatex.pdf>. The `\url` command is provided by the package `url`.

5 We have several FONTS *at disposal*

The serifed roman font is used for the main body of the text. *Italics are typically used to denote emphasis or quotations.* The teletype font is typically used for source code listings. The **bold**, SMALL-CAPS and sans-serif variants of the base roman font can be used to denote specific types of information.

We can also change the font size, although it is usually not necessary.

A wide variety of mathematical fonts is also available, such as:

ABC, *ABC*, **ABC**, ABC, ABC, ABC

By loading the amsfonts packages, several additional fonts will become available:

ℳℳℳ, ABC

Many other mathematical fonts are available¹.

1. See <http://tex.stackexchange.com/a/58124/70941>.

6 Inserting the bibliography

After loading the `biblatex` package and linking a bibliography database file to the document using the `\addbibresource` command, you can start citing the entries. This is just dummy text [1] lightly sprinkled with citations [2, p. 123]. Several sources can be cited at once [3–5]. “Fundamental Algorithms” was written by Knuth in 1973. We can also produce Knuth [1] or (Knuth [1], 1973). The full bibliographic citation is: *Donald E. Knuth. “Fundamental Algorithms”. In: Second. Vol. 1. The Art of Computer Programming. This is a full INBOOK entry. Reading, Massachusetts: Addison-Wesley, Oct. 1973. Chap. 1.2, pp. 10–119.* We can easily insert a bibliographic citation into the footnote¹.

The `\nocite` command will not generate any output, but it will insert its argument into the bibliography. The `\nocite{*}` command will insert all the records in the bibliography database file into the bibliography. Try uncommenting the command and watch the bibliography section come apart at the seams.

When typesetting the document for the first time, citing a work will expand to `[work]` and the `\printbibliography` command will produce no output. It is now necessary to generate the bibliography by running `biber sci-pdflatex.bcf` from the command line and then by typesetting the document again twice. During the first run, the bibliography section and the citations will be typeset, and in the second run, the bibliography section will appear in the table of contents.

The `biber` command needs to be executed from within the directory, where the \LaTeX source file is located. In Windows, the command line can be opened in a directory by holding down the `Shift` key and by clicking the right mouse button while hovering the cursor over a directory. Select the `Open Command Window Here` option in the context menu that opens shortly afterwards.

With online services – such as Overleaf – all commands are executed automatically.

1. Donald E. Knuth. “Fundamental Algorithms”. In: Second. Vol. 1. The Art of Computer Programming. This is a full INBOOK entry. Reading, Massachusetts: Addison-Wesley, Oct. 1973. Chap. 1.2, pp. 10–119.

Bibliography

- [1] Donald E. Knuth. "Fundamental Algorithms". In: Second. Vol. 1. *The Art of Computer Programming*. This is a full INBOOK entry. Reading, Massachusetts: Addison-Wesley, Oct. 1973. Chap. 1.2, pp. 10–119.
- [2] Daniel D. Lincolll. "Semigroups of Recurrences". In: *High Speed Computer and Algorithm Organization*. Ed. by David J. Lipcoll, D. H. Lawrie, and A. H. Sameh. Third. Fast Computers 23. This is a full INCOLLECTION entry. New York: Academic Press, Sept. 1977. Chap. 3, pp. 179–183.
- [3] David J. Lipcoll, D. H. Lawrie, and A. H. Sameh, eds. *High Speed Computer and Algorithm Organization*. Third. Fast Computers 23. This is a cross-referenced BOOK (collection) entry. New York: Academic Press, Sept. 1977.
- [4] *The Definitive Computer Manual*.
- [5] Larry Manmaker. *The Definitive Computer Manual*. Silver. This is a full MANUAL entry. Chips-R-Us. Silicon Valley, Apr. 1986.
- [6] Jill C. Knvth. *The Programming of Computer Art*. Vernier Art Center. This is a full BOOKLET entry. Stanford, California, Feb. 1988.

7 Inserting the index

After using the `\makeindex` macro and loading the `makeidx` package that provides additional indexing commands, index entries can be created by issuing the `\index` command. It is possible to create ranged index entries, which will encompass a span of text. To insert complex typographic material – such as α or \TeX – into the index, you need to specify a text string, which will determine how the entry will be sorted. It is also possible to create hierarchical entries.

After typesetting the document, it is necessary to generate the index by running

```
texindy -I latex -C utf8 -L  $\langle locale \rangle$  sci-pdflatex.idx
```

from the command line, where $\langle locale \rangle$ corresponds to the main locale of your thesis – such as `english`, and then typesetting the document again.

The `texindy` command needs to be executed from within the directory, where the \LaTeX source file is located. In Windows, the command line can be opened in a directory by holding down the `[Shift]` key and by clicking the right mouse button while hovering the cursor over a directory. Select the `[Open Command Window Here]` option in the context menu that opens shortly afterwards.

With online services – such as Overleaf – the commands are executed automatically, although the locale may be erroneously detected, or the `makeindex` tool (which is only able to sort entries that contain digits and letters of the English alphabet) may be used instead of `texindy`. In either case, the index will be ill-sorted.

Index

α , 15

dummy text, 15

T_EX, 15

vehicles

 speed cars, 15

 trucks, 15

A An appendix

Here you can insert the appendices of your thesis.